

BSD-IEC-0101FT-SC

1 10/100/Base-TX to 100-FX (SC) Industrial Converter

- DNV Type approved for ships, craft and off-shore platform
- UTP to Fiber Media Converter
- RJ-45 port support Auto MDI/MDI-X Function
- Auto Negotiation Speed, Half/Full Duplex
- Store-and-Forward Switching Architecture
- Wide temperature model supports -40°C~75°C
- Built-in Link Lose Forwarding(LLF) & Link Fault Pass-Through (LFP) Technology
- Wide-range Redundant Power Design
- Overload current resettable Fuse Present
- Power Polarity Reverse Protect
- IP-30 Protection
- DIN Rail and Wall Mount Design
- Provides EFT protection 3000 VDC for power line
- Supports 6000 VDC Ethernet ESD protection



In Stock

BSD-IES-0005T Industrial 5 Port 10/100-TX Entry Level Switch



- BSD-IES-00005M provide 5x10/100Base-T(X) ports
- Supports 5 ports 10/100 Base-T(X)
- Supports auto-negotiation and auto-MDI/MDI-X
- Supports store and forward transmission
- Supports flow control
- Compact size for easy installation
- Rigid IP-30 housing design
- DIN-Rail and wall mounting design
- Redundant power supply



BSD-SFPGLC

1.25 Gbps, 3.3V 1000Base-FX Multi Mode:1310 nm 2 km and 850 nm 500m Single Mode SFP module 20+ KM



- SFP package with LC connector
- 1310nm FP laser and PIN photo detector
- 2km transmission with MMF
- 20Km transmission with SMF (**BSD-SFPGLC-20**)
- +3.3V single power supply
- LVPECL compatible data input/output interface
- Low EMI and excellent ESD protection
- Laser safety standard IEC-60825 compliant
- Compatible with RoHS
- **CISCO, HP, major brands coding available**