

## PoE Injector

### Description:

The PoE Injector BSD-PS150S fully complies with IEEE 802.3af standard, and can work with all IEEE 802.3af PoE compliant PDs (Powered Devices), PoE Receiver Adapters, or other equivalent product, to expand your network where there are no power line or outlet, where you wish to fix device such as AP, IP Camera or IP Phone, etc.



### Features:

- IEEE 802.3af compliant
- Delivers power up to 100 meters
- Auto-determine the necessary power requirements
- Plug-and-Play, requires no configuration
- External power adapter supply

<b>Interface</b>	2 10/100/1000Mbps RJ45 Port AUTO Negotiation/AUTO MDI/MDIX 1 48VDC POWER INPUT PORT
<b>Network Media</b>	10BASE-T: UTP category 3, 4, 5 cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 100BASE-TX: UTP Category 5, 5e cable (Max 100m) EIA/TIA-568 100Ω STP (Max 100m) 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)
<b>Dimensions (W X D X H)</b>	3.2*2.1*0.9 in.(80.8*54*24 mm)
<b>LED Indicator</b>	PWR
<b>Power Supply</b>	15.4W (Max. 48VDC)
<b>Basic Function</b>	Compatible With IEEE 802.3af Compliant PDs Delivers Power Up To 100 Meters Auto-Determine The Necessary Power Requirements
<b>Certification</b>	FCC, CE, RoHS
<b>System Requirements</b>	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
<b>Environment</b>	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

### Ordering Information

<b>BSD-PS150S</b>	BSD 10/100/1000TX PoE Injector 15W max
-------------------	--