

## 8 PoE 10/100TX + 4 GIGA SFP PORT MANAGED INDUSTRIAL SWITCH

### Overview

BSD-IPES-3408GSFP is a high performance L2+ industrial Gigabit uplink switch which provides L2 wire speed and advanced security function for network aggregation deployment. It delivers ITU G.8032 ring recovery less than 50ms, comprehensive QoS, IGMPv1/v2/v3 & routing. It also supports Cisco Discovery Protocol (CDP) and LLDP for Ciscoworks to detect the switch info and show on L2 map topology. The switch also has the RTC (real time clock) which can keep track of time always.

BSD-IPES-3408GSFP supports IEEE802.3at/af standard which can feed HI-power up to 30W/52V; 15W/48V at each PoE port for big power consumption devices like PTZ IP camera, High power wireless AP etc. PoE scheduling allows pre-set power feeding schedule upon routine time table. PoE per port status shows voltage, current, watts info as well as to enable / disable ports. The BSD-IPES-3408GSFP DIDO function can support additional open/close physical contact for designate applications besides Port / Power events such as triggering an alarm if the switch is moved or stolen. In case of events, the switch will immediately send an email & SMS text message to pre-defined addresses as well as SNMP Traps out. The optional environmental monitoring can detect switch overall temperature, voltage and current where can send the SNMP traps, email and SMS alert when abnormal.

The BSD-IPES-3408GSFP is designed with redundant power supply at 46~56VDC. Featured with relay contact alarm function, this switch is able to connect with alarm system in case of power failure. The BSD-IPES-3408GSFP also provides 3000V EFT and 6000V ESD protection, which can reduce unstable situation caused by power line and Ethernet.



### Key Features

- 4 1000 SFP +8 10/100TX L2 plus PoE Managed Industrial Switch (Total 12 Ports Switch)
- Supports IEEE802.3at/af feeding power up to 30W/52V; 15W/48V per PoE port at 46~56VDC
- Back-plane (Switching Fabric):9.6Gbps
- 16K MAC address table
- DDM to support SFP diagnostic function (optional)
  - Automatically convert the raw data into dB values for TX power/RX power, making it easier to measure the fiber distance*
- 10KB Jumbo frame supported on 10/100MTX
- PoE management including PoE scheduling and device detection
- PoE per port status including ON/OFF, voltage, current and watts
- User friendly UI, Auto topology drawing, topology demo
- ITU G.8032 Ring protection in 50ms < 256 switches
  - Support various ring/chain topologies, including double ring*
  - Ring protection coverage data*
  - Miss-wiring avoidance*
  - LED indicator*
  - Email, traps, or SMS notification*
  - Repowered auto ring restore*
  - Ensure the switches in a ring to survive after power break-out is back*
  - The status can be shown in NMS when each switch is back*
- Provides EFT protection 3000 VDC for power line.
- Supports 6000 VDC Ethernet ESD protection
- Provides ground isolation & DC to DC power isolation with 1500VDC
- LACP load balancing to distribute the load
- Built-in RTC(Real Time Clock)
- Supports IEEE 802.1p Class of Service, per port provides 8 priority queues Port base, Tag Base and Type of Service Priority

- IEEE 802.1d STP, IEEE 802.1w RSTP,802.1s MSTP VLAN redundancy
- 4K 802.1Q VLAN, Port based VLAN, GVRP\*, QinQ
  - Supports IEEE 802.1ab LLDP, Cisco CDP; LLDP info can be viewed via Web/Console/IntriView (optional)
- DHCP server / client / Bandwidth Control
  - Ingress Packet Filter and Egress Rate Limit*
  - Broadcast/Multicast Packet Filter Control*
- TFTP/HTTPs firmware upgrade; Redundant firmware (optional) to avoid crashing in case of upgrading failure
- System Event Log, SMTP Email alert and SNMP Trap for alarm support; 32 RMON counters
- Relay Alarm Output System Events
- Security
  - SSL/SSH/ACL L2&L3*
  - Port Security: MAC address entries/Filter/MAC-IP-Port binding*
  - IP Security: IP address security management to prevent unauthorized intruder.*
  - Management access control with priority*
  - Login Security: IEEE802.1X/RADIUS*
- Multicast static route for non- IGMP camera to prevent flooding;
- IGMP router port to assign query in ring
- Multicast VLAN registration for metro video
- IGMPv1,v2,v3 with Query mode for Multi Media
- Factory reset button to restore setting to factory default
- Watchdog design to auto reboot switch CPU is found dead
- Optional environmental monitoring for system input voltage, current, ambient temperature
- Supports DIDO(Digital Input/Digital Output)
- IP30 metal housing with DIN rail design

## Hardware Specifications

<b>Standards</b>	IEEE 802.3 10Base-T Ethernet, IEEE 802.3u 100Base-TX, IEEE802.3z Gigabit fiber IEEE802.3x Flow Control and Back Pressure, IEEE802.3ad Port trunk with LACP IEEE802.1d Spanning Tree, IEEE802.1w Rapid Spanning Tree IEEE802.1s Multiple Spanning Tree IEEE 802.3ad Link Aggregation Control Protocol (LACP), IEEE 802.1AB Link Layer Discovery Protocol (LLDP) IEEE 802.1X User Authentication (Radius), IEEE802.1p Class of Service, IEEE802.1Q VLAN Tag, IEEE802.3at/af Power over Ethernet
<b>Switch Architecture</b>	Back-plane (Switching Fabric): 9.6Gbps Packet throughput ability (Full-Duplex): 23.8Mpps @64bytes
<b>Transfer Rate</b>	14,880pps for Ethernet port 148,800pps for Fast Ethernet port 1,488,000pps for Gigabit Fiber Ethernet port
<b>Mac Address</b>	16K MAC address table
<b>Jumbo frame</b>	10KB for 10/100TX ports
<b>Connectors</b>	10/100TX: 8 x RJ-45 type connector Mini-GBIC: 4 x 1000 SFP Sockets Power & P-Fail connector: 1 x 6-pole terminal block RS-232 connector: 1 x RJ-45 type connector
<b>Network Cable</b>	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5/ 5E cable EIA/TIA-568 100-ohm (100m)
<b>Optical Cable</b>	Multi-mode: 50/125um~62.5/125um; Single mode: 9/125um Wavelength: 850nm (Multi-mode) / 1310nm (Single-mode)
<b>Protocol</b>	CSMA/CD
<b>PoE pin assignment</b>	RJ-45 port # 1~#8 support IEEE 802.3at/af End-point, Alternative A mode. Per port provides 30W at 52~56VDC/15W at 48V~56VDC. Positive (VCC+): RJ-45 pin 1,2. Negative (VCC-): RJ-45 pin 3,6.
<b>LED</b>	Per unit: Power 1 (Green), Power 2 (Green), P-Fail (Red) Ethernet port: Link/Activity (Green), Speed (Green); Mini-GBIC: Link/Activity (Green)
<b>DI/DO</b>	2 Digital Input (DI) : Level 0: -30~2V / Level 1: 10~30V Max. input current:8mA 2 Digital Output(DO): Open collector to 40 VDC, 200mA
<b>Operating Humidity</b>	5% ~ 95% (Non-condensing)
<b>Operating Temperature</b>	-20°C~-60°C / -4°F~140°F (Standard model) -40°C~-75°C / -40°F~167°F(-E model)
<b>Storage Temperature</b>	-40°C~85°C / -40°F~185°F
<b>Power Supply</b>	46~56VDC, Redundant power input with 1500VDC isolation -48VDC is single power input
<b>Power Consumption</b>	10W
<b>PoE Power Budget</b>	240W
<b>Dimensions</b>	Metal case. IP-30, 66 (W) x 114 (D) x 152 (H) mm . Weight 900g
<b>Installation</b>	DIN Rail
<b>EMI &amp; EMS</b>	FCC Class A, CE EN61000-6-2, CE EN61000-6-4, CE EN61000-4-2, CE EN61000-4-3, CE EN61000-4-4, CE EN61000-4-5, CE EN61000-4-6, CE N61000-4-8, EN61000-4-11
<b>Stability Testing</b>	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)
<b>MTBF</b>	292,619 hrs
<b>Warranty</b>	5 years

## Software Specifications

<b>Management</b>	SNMP v1 v2c, v3/ Web/Telnet/CLI
<b>SNMP MIB</b>	RFC 1215 Traps MIB, RFC 1213 MIBII, RFC 1157 SNMP MIB, RFC 1493 Bridge MIB, RFC 2674 VLAN MIB, RFC 1643 EtherLike, RFC 1757 RMON, RSTP MIB, Private MIB, LLDP MIB
<b>ITU G.8032</b>	Support ITU G.8032 v2 for Ring protection in less than 50ms for self-heal recovery < 256 switches which can be compatible with other ITU G.8032 metro switches Support various ring/chain topologies Ring covers data & packets
<b>User friendly UI</b>	Auto topology drawing , Topology demo DDM threshold monitoring with dB values (optional)
<b>Port Trunk with LACP</b>	LACP Port Trunk: 4 Trunk groups/Maximum 4 trunk members
<b>LLDP</b>	Supports LLDP to allow switch to advise its identification and capability on the LAN
<b>CDP</b>	Cisco Discovery Protocol for topology mapping
<b>PoE Port status</b>	PoE Detection to check if PD is hang up then restart the PD PoE Scheduling to On/OFF PD upon routine time table Per port PoE status for ON/OFF, voltage, current and watts
<b>VLAN</b>	Port Based VLAN IEEE 802.1Q Tag VLAN (256 entries)/ VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096). QinQ
<b>IPv6/4</b>	Present
<b>Spanning Tree</b>	Supports IEEE802.1d Spanning Tree and IEEE802.1w Rapid Spanning Tree, IEEE802.1s Multiple Spanning Tree
<b>Quality of Service</b>	The quality of service determined by port, Tag and IPv4 Type of service, IPv4 Different Service
<b>Class of Service</b>	Support IEEE802.1p class of service, per port provides 8 priority queues
<b>IP Security</b>	Supports 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder.
<b>Login Security</b>	Supports IEEE802.1X Authentication/RADIUS
<b>Port Mirror</b>	Support 3 mirroring types: "RX, TX and Both packet"
<b>Network Security</b>	Support 10 IP addresses that have permission to access the switch management and to prevent unauthorized intruder. 802.1X access control for port based and MAC based authentication/MAC-IP-Port binding Management access control with priority.256 Policy based Access Control List SSL/ SSH for Management,
<b>IGMP</b>	Support IGMP v1,v2,v3 with snooping and query; Supports static multicast routing 256. IGMP router port for assign another query
<b>Multicast VLAN Registration</b>	MVR enables multicast packets go through VLAN for VOD application
<b>Bandwidth Control</b>	Support ingress packet filter and egress packet limit. The egress rate control supports all of packet type. Ingress filter packet type combination rules are Broadcast/Multicast/Flooded Unicast packet, Broadcast/Multicast packet, Broadcast packet only and all types of packet. The packet filter rate can be set an accurate value through the pull-down menu for the ingress packet filter and the egress packet limit.

# BSD-IPES-3408GSFP

## Software Specifications

<b>RTC</b>	Built-in Real Time Clock to keep track of time always
<b>Flow Control</b>	Supports Flow Control for Full-duplex and Back Pressure for Half-duplex
<b>System Log</b>	Supports System log record and remote system log server
<b>SMTP/Text SMS</b>	Supports SMTP Server and 6 e-mail accounts for receiving event alert; can send SMS text alert via mobile
<b>Relay Alarm</b>	Provides one relay output for port breakdown, power fail and alarm. Alarm Relay current carry ability: 1A @ DC24V
<b>Protection</b>	Miss-wiring avoidance Repowered auto ring restore Loop protection
<b>SNMP Trap</b>	Up to 3 trap stations; trap types including: Device cold start, Authorization failure, Port link up/link down, DI/DO open/close PoE port event, Environmental abnormal
<b>DHCP</b>	Provide DHCP Client/ DHCP Server
<b>DNS</b>	Provide DNS client feature and support Primary and Secondary DNS server.
<b>SNTP</b>	Supports SNTP to synchronize system clock in Internet
<b>Firmware Update</b>	Supports TFTP firmware update, TFTP backup and restore.
<b>Configuration upload and download</b>	Supports text configuration file for system quick installation; Support factory reset button to restore all settings back to factory default
<b>IfAlias</b>	Each port allows an alphabetic string of 128-byte assigned as its own unique name via the SNMP or CLI interface

## Ordering Information

**BSD-IPES-3408GSFP:** Industrial 8 10/100TX PoE + 4 Giga SFP Port Managed Ethernet Switch (-20 ° C to 60 ° C operating temperature)

**BSD-IPES-3408GSFP-E:** Industrial 8 10/100TX PoE + 4 Giga SFP Port Managed Ethernet Switch (-40 ° C to 75 ° C wide operating temperature)

**BSD-SFPGLC(SX):** 1.25 G 850nm 1000Base Multimode LC SFP Module 500m

**BSD-SFPGLC:** 1.25 G 1310 nm 1000Base Multimode LC SFP Module 2km

**BSD-SFPGLC-20;** 1.25G 1310nm 1000Base Singlemode LC SFP Module 20 km

**Add D for DDM SFP**